

TECHNICAL DATA SHEET

SF03 GIBSON SHOE



DESCRIPTION

Ideal for managers or as a uniform shoe, the Gibson shoe features a leather upper with padded ankle support. It has both steel toe cap and midsole protection and the hardwearing, dual density PU sole is shock absorbent, anti-slip and fuel oil resistant.

SIZES

UK 3-13

STANDARDS

EN20345 SB-P SRC

KEY FEATURES

- Leather upper with padded ankle
- Steel toe cap and midsole
- Dual density shock absorbent, anti-slip and fuel oil resistant PU sole
- Energy absorbing heel reduces foot fatigue

FEATURE ICONS



TECHNICAL DATA SHEET

MATERIALS

- Leather upper
- PU/PU sole
- Steel toe cap
- Steel midsole

TYPICAL INDUSTRIES

- Uniform
- Transport
- Warehousing
- Emergency services

CERTIFICATION/MARKINGS



EN ISO 20345:2011 is an internationally recognised standard which specifies requirements for safety footwear. Any product which references an EN standard must have the relevant certification attributed to the product code found on the product.

The product standard can be found on the tongue label and should match that stated on the certification. The standard is usually a group of numbers and letters, for example S3 WR HRO SRC. These letters and numbers denote the characteristics that make up the footwear you are buying which include properties such as protective toe cap, water-resistant uppers, protective midsole, fuel oil resistance, anti-static, heat resistance and slip resistance.

Users are advised to select the required class of performance based on the risk assessment of the location and/or task as appropriate.

PRODUCT DETAILS

CODE	SIZE	COLOUR	BARCODES	PACKAGING
SF0303	3	Black	5019200001200	Each pair individually boxed Purchase multiple: 1 Outer carton quantity: 10 
SF0304	4	Black	5019200001217	
SF0305	5	Black	5019200001224	
SF0306	6	Black	5019200001231	
SF0307	7	Black	5019200001248	
SF0308	8	Black	5019200001255	
SF0309	9	Black	5019200001262	
SF0310	10	Black	5019200001279	
SF0311	11	Black	5019200001286	
SF0312	12	Black	5019200001293	
SF0313	13	Black	5019200001309	